



**IPC**

BY TENNANT COMPANY

SCRUBBER DRIERS - WALK BEHIND

# CT5

MAX PRODUCTIVITY

900 m<sup>2</sup>/h

BATTERIES  
RUNNING TIME

75 min.

WATER TANK  
RUNNING TIME

25 min.  
working session



**ECO SELECT**



**LI-ION  
BATTERY**



**RDS  
REVERSE DRY SYSTEM**



## INNOVATIONS



RDS  
REVERSE  
DRY  
SYSTEM



ANC™  
ADVANCED  
NOISE  
CONTROL



SLS™  
SELF  
LEVELING  
SYSTEM



ECO  
SELECT



LI-ION  
LITHIUM  
BATTERY

## SPEC



CT5 CAN BE STORED, TRANSPORTED AND PARKED IN EVERY SPACE IN JUST FEW SECONDS.



RECHARGEABLE LITHIUM-ION BATTERY BOTH ON BOARD THE MACHINE AND EXTERNALLY



THE RDS ALLOWS TO WASH AND DRY EASILY EVEN IN POINTS WHERE OTHER MACHINES DO NOT REACH

MOST FREQUENTLY USED



RETAIL



HOSPITALITY



BUILDING SERVICE CONTRACTORS



TECHNICAL DATA

CT5 B28

PERFORMANCE

Max theoretical productivity	m <sup>2</sup> /h	900
Cleaning path	mm	280
Water tank capacity (solution recovery)	l	5 - 5
Max running time	min	75
Voltage	V	36
Installed power	W	220
Brush pressure	kg	12
Squeegee width	mm	300
Max speed	km/h	3.5
Weight	kg	20.2
Dimension (LxWxH)	mm	758 x 376 x 392

CONSUMABLES

BRUSHES



SPPV02580 | POLYPROPYLENE (PP) SOFT BRUSH  
 SPPV02438 | POLYPROPYLENE (PP) MEDIUM BRUSH  
 SPPV02581 | POLYPROPYLENE (PP) HARD BRUSH

PADS  
(BOX OF 5)



SPPV02583 | 11" POLISH PAD - WHITE  
 SPPV02584 | 11" BUFF PAD - RED  
 SPPV02585 | 11" MEDIUM DUTY PAD - GREEN  
 SPPV02586 | 11" STRIPPING PAD - BROWN  
 SPPV02582 | PAD DRIVER

SQUEEGEE BLADES



KTRI06090 | LATEX BLADE  
 KTRI06092 | LINATEX BLADE